



**MADE IN THE USA**



**Our goal is to provide an engineered wood flooring product designed to your unique specification – in terms of color, species, grade selection, dimension, and performance. Our material is manufactured in Wisconsin and available at a price point and lead time well suited for commercial projects. Please contact us and we will arrange a visit to review our offering and prepare your project sample request.**

**BUILD-A-FLOOR**  
**PROJECT SPECIFIC PRODUCT REQUEST**

**CORE:**

- HDF (High Density Wood Fiber Board-750kg/cubic meter)
- Multi Ply Birch Plywood

**OVERALL THICKNESS:**

- 3/8"  5/8"
- 1/2"  3/4"

**BOARD WIDTH:**

- 5"  7.5"
- 6.3"  8"

**BOARD LENGTH\*:**

- Random lengths up to 47.5"
- Random lengths up to 71.5"
- Random lengths up to 95.5" (plywood only)
- \*Shortest length for all is 12"

**EDGE PROFILE:**

- Tongue & Groove
- Valinge 2G Click ( Available on 5" width HDF Core only)

**FINISH WEAR RESISTANCE:** (ASTM D4060 modified with S-42 sandpaper strips changed every 500 cycles.)

- Residential - 1000 - 1500 revolutions
- Residential Plus - 1600-2000 revolutions
- Light Commercial - 4000 - 5000 revolutions

**FACE VENEER SPECIE:**

- White Oak  Maple  Hickory
- Red Oak  Walnut  Other \_\_\_\_\_

**FACE VENEER GRADE:**

- Select and better  #2 Common and better (Heavy character)
- #1 Common and better

**FACE VENEER THICKNESS:**

- .8mm  3mm
- 2mm  4mm

**FACE VENEER SURFACE TEXTURE:**

- Smooth
- Lightly Wire Brushed
- Medium Wire Brush

**INSTALLATION TYPE:**

- Glue Down  Nailed/Stapled
- Floating

**GLOSS LEVEL:**

- Matte 4-6%  Medium 20-23%
- Low 9-11%  High 44-46%

**ADDITIONAL NOTES:**